



技术参数:

标志:

- 插针数: 8+PE
 - 额定电流: 10A
 - 额定电压: ~50V/-250V
 - 额定脉冲电压: 0.8kV
 - 污染等级: 3
 - 依据UL/CSA的额定电压: 50V
 - 额定电压(直流电压): 120V
 - 绝缘阻抗: $>10^{10}\Omega$
 - 材料: 聚碳酸酯
 - 颜色: RAL 7032 (浅灰色)
 - 温度范围: $-40^{\circ}\text{C} - +125^{\circ}\text{C}$
 - 依据UL 94的阻燃等级: V0
 - 可插拔次数: >500
- 插针:**
- 接线方式: 冷压连接
 - 材料: 铜合金
 - 表面处理:
 - 镀银
 - 镀金
 - 接触电阻: $<3\text{m}\Omega$
 - 线径范围: $0.14-2.5\text{mm}^2(26-14\text{ AWG})$
 - 工具:
 - 冷压钳: TL02G
 - 送针器: TL00

Technical specification:

Insters:

- No. of contact: 8+PE
 - Rated current: 10A
 - Rated voltage: ~50V/-250V
 - Rated impulse voltage: 0.8kV
 - Pollution degree: 3
 - Rated voltage acc.to UL/CSA: 50V
 - Rated voltage(direct voltage): 120V
 - Insulation resistance: $>10^{10}\Omega$
 - Material: polycarbonate
 - Colour: RAL 7032(light grey)
 - Temperature range: $-40^{\circ}\text{C} - +125^{\circ}\text{C}$
 - Flammability acc.to UL 94: V0
 - Mating cycles: >500
- Contacts:**
- Terminal: crimp terminal
 - Material: copper alloy
 - Surface:
 - Hard-silver plated
 - Hard-gold plated
 - Contact resistance: $<3\text{m}\Omega$
 - Wire gauge: $0.14-2.5\text{mm}^2(26-14\text{ AWG})$
- Tools:**
- Crimp contact tool: TL02G
 - Contact removal tool: TL00

						表面处理 Finish		-		图号 Drawing No.		-	
						材料 Material		-		产品代号 Part Code		HD-008-FC	
标记 Mark	数量 Number	变更描述/Description		签名 Signature	日期 Date	比例 Scale		版本 REV.	重量 Weight	数量 Qty.	产品料号 Part No.		1250080200001
绘图 Drawn	BQ LUO	姓名/Name	日期/Date	姓名/Name	日期/Date	1:1	V1.0	8g	-	产品名称 Part Name		-	
审核 Checked	P RAO	姓名/Name	日期/Date	姓名/Name	日期/Date	1:1		V1.0		8g		-	
工艺 Process	-	姓名/Name	日期/Date	姓名/Name	日期/Date	1:1		V1.0		8g		-	
												厦门唯恩电气有限公司 XIAMEN WAIN ELECTRICAL CO.LTD	